

AGGREGATE LIFTING TABLE

FOOT-HYDRAULIC

The foot-hydraulically operated aggregate lifting table can be used universally, making it ideal for the safe removal and instal-

lation of engines, gearboxes, HV batteries and chassis components from various manufacturers.

- + Top entry level model
- + High stability
- + Flexible application

Safety: The large footprint of the Master Gear lift tables provides high stability, enabling safe and precise work.

Easy to manoeuvre with load.

Can be combined with various on-site attachments - making the Master Gear S3 1.0 the comfortable workshop assistant.

Easy handling: Large wheels ensure mobility in the workplace.




Universally applicable: Also perfectly usable as a workbench.

The uniformly distributed threaded holes are cleaned up for attaching a wide variety of supports.

Flat, slim design for free positioning under the vehicle.

HIGHLIGHTS IN DETAIL



1 The mounting plate VarioDesk can be tilted in the transverse direction by $\pm 2^\circ$



2 and can be moved ± 20 mm in the longitudinal and transverse direction.

3 The integrated lowering brake valve allows an exact dosing of the lowering speed. The load stroke is foot hydraulic.

4 Four castors (2 with integrated parking brakes).

5 Optional: lift table with pull-out handle. This allows moving the lifting table even when transporting a large, protruding battery in the lowered state.

MASTER GEAR S3 1,0



Model	Master Gear S3 1,0
Capacity	1 t
Stroke	1330 mm
F Usable Table length max.	1260 mm
E Usable table width max.	740 mm
C Length	1644 mm - 2044 mm*
A Width	740 mm
D Height	635 mm
B Height max.	1965 mm
Weight	290 kg

* Optional: Lift table with pull-out handle

SPECIFICATION

SIMILAR PRODUCTS



Premium Version:
Master Gear MGO